



Compensati per Autotrasporti
PLYWOOD FOR ROAD TRANSPORT - SAN WIRE - LIGHT BROWN



Compensati per Autotrasporti

SAN WIRE

Compensato di betulla ricoperto con film fenolico, studiato per l'utilizzo specifico nel settore autotrasporti. Questo prodotto garantisce omogeneità di finitura superficiale, elevata durezza delle superfici, ottimo grado antiscivolo e, grazie alla sua particolare composizione, offre una risposta ottimale alle sollecitazioni meccaniche alla flessione, alla trazione ed all'elasticità.

Birch plywood coated with phenolic film, especially conceived for the road transport industry. This product has uniform surface finish, high surface hardness, is slide-proof and particularly resistant to bending and traction, resilient under mechanical stress.

COMPOSIZIONE COMPOSITION

I pannelli sono composti da sfogliati da 1,5 mm incollati tra loro con fibra incrociata ricoperti con film fenolico nero cono finitura anti-scivolo.

The panels are composed of 1.5 mm veneer sheets, glued together in cross-grain pattern, coated with black phenolic film, with slide-proof finish.

FILM FENOLICO PHENOLIC FILM

Film 220 g/m² superficie superiore zigrinata
Film 220 g/m² superficie inferiore liscia

220 g/sq m film with knurled upper surface
220 g/sq m film with smooth lower surface

INCOLLAGGIO GLUEING

Fenolico - classe 3 (EN-314)

Phenolic-resin glue - Class 3 (EN-314)

QUALITÀ QUALITY

BB/BB

BB/BB

TOLLERANZE SPESSORI THICKNESS TOLERANCES

± 0,2 mm

± 0,2 mm

TOLLERANZE DIMENSIONI SIZE TOLERANCES

Conforme a norme UNI EN 315

In conformity with norms UNI EN 315

PESO SPECIFICO SPECIFIC WEIGHT

740 Kg/m³

740 Kg/m³

RILASCIO DI FORMALDEIDE FORMALDEHYDE RELEASE

Conforme a norme europee

In conformity with European norms

FORMATI STANDARD SAN WIRE - A STANDARD SIZES SAN WIRE - A

mm 1200/1220/1250/1500/1530 x 2150/2500

mm 1200/1220/1250/1500/1530 x 2150/2500

FORMATI STANDARD SAN WIRE - B STANDARD SIZES SAN WIRE - B

mm 1200/1250/1500/1530 x 2700/3050/3700/4000

mm 1200/1250/1500/1530 x 2700/3050/3700/4000

FORMATI SPECIALI SPECIAL SIZES

Misure speciali su richiesta (massimo mm 2050x5200)

Special sizes are available up to 2050 x 5200 mm max.

SPESSORI THICKNESSES

mm 6,5 - 9 - 12 - 15 - 18 - 21 - 24 - 27 - 30 - 35

mm 6,5 - 9 - 12 - 15 - 18 - 21 - 24 - 27 - 30 - 35

FINITURE AVAILABLE FINISHES

Disponibili diverse colorazioni per ordini continuativi.
Possibile applicazione di un logo sulla superficie.

Different colors are available for serial orders.
A logo can be applied on the surface.

SERVIZI SERVICE

Servizio CNC, rivestimenti particolari a richiesta

CNC service, special cladding on request.

LIGHT BROWN

Sempre relativo al settore autotrasporti, studiato per le fiancate interne dei mezzi furgonati, è stato introdotto un nuovo prodotto con finitura fenolica "LightBrown" che offre maggiore resistenza alla penetrazione di umidità e aumenta la durezza del legno al fine di preservarlo. Si presenta con una finitura superficiale liscia su entrambi i lati, leggermente lucida e di colore marrone, lasciando comunque intravedere le venature del legno sottostante.

Designed for the road transport, a new product is available for the inner side walls of vehicles with phenolic finish called "Light Brown", which is more wetness-proof and increases the wood hardness, ensuring a longer life. Its surface is smooth on both sides, slightly glossy and brown-colored, with the wood veins still visible underneath.